

Product Datasheet

MAXI DESKTOP UNITS



PRODUCT DESCRIPTION

The MAXI desktop is designed to be a compact unit, offering mixed choices of individually fused UK power sockets, and a powerful 3.4A USB A+C charger, as well as data & multimedia options

- Dual A+C US/b charger, with Quick Charge 3.0, and Power Delivery
- Tough extrusion in a RAL 9003 finish
- 45° angled sockets, can accept large plugs and transformers
- Conforms to BS6396 and BS1363
- Certified to BS5733
- 500mm power lead to male 3-pole connector

STANDARD PRODUCTS

| Part Code | Description | Dimensions |
|------------------|---|-----------------|
| MAXI DESK 2/26CU | 2 x 5A sockets, dual 3.4A USB A+C, 2 x 6C cut-outs | 270 x 72 x 78mm |
| MAXI DESK 2/2SU | 2 x 5A sockets, dual 3.4A USB A+C, 2 x Cat 6 couplers | 270 x 72 x 78mm |
| MAXI DESK 3/U | 3 x 5A sockets, dual 3.4A USB A+C | 270 x 72 x 78mm |
| MAXI DESK 3/26C | 3 x 5A sockets, 2 x 6C cut-outs | 270 x 72 x 78mm |
| MAXI DESK 3/2S | 3 x 5A sockets, 2 x Cat 6 couplers | 270 x 72 x 78mm |
| MAXI DESK 4 | 4 x 5A sockets | 270 x 72 x 78mm |

INSTALLATION



All desktop units come with 2 methods of attaching to the desktop. Fix to the desk with either a pair of G-Clamps, or using adhesive pads.

The clamps come with an optional rubber guard to protect the desk

USAGE & MAINTENANCE

Not to be used with products and appliances exceeding 5A

Fuses are 5x20mm and can be user-replaced.

To replace a fuse, disconnect the unit from the mains first.

To clean unit, disconnect from the mains, and wipe with a clean damp cloth

TECHNICAL SPECIFICATION

| | |
|-------------------|--|
| In the box | 1x Desktop unit; pair of clamps; pair of adhesive pads |
| Construction | PVC extrusion, PVC sockets and fascias |
| Max voltage | 250V |
| Fuse rating | 3.15A or 5A |
| Fuse size/type | 5x20mm ceramic slow blow |
| USB | USB output type A and type C, Max 18W USB A: QC3.0, DC 5V3A, 9V2A, 12V1.5A USB C: PD, DC 5V3A, 9V2A, 12V1.5A A+C together: DC5V3.4A |
| Mains lead length | 500mm |
| Mains lead spec | 1.5mm ² HO5VV-F |
| Mains connector | 20A male 3-pole connector |
| Conformities | BS 1363; BS 6396:2008; BS 5733; IEC60884-1:2006; UL 94V-0 |
| Switch | Single pole with neon indicator |
| Compliances | RoHS; WEEE; CE; UKCA |