

Product Datasheet

MINI DESKTOP UNITS



PRODUCT DESCRIPTION

The MINI desktop is designed to be a compact unit, offering mixed choices of individually fused UK power sockets, and a powerful 18W USB A+C charger

- Dual A+C USB charger, with Quick Charge 3.0, and Power Delivery
- Tough extrusion
- 45° angled sockets, can accept large plugs and transformers
- Conforms to BS6396 and BS1363
- Certified to BS5733
- 500mm power lead to male 3-pole connector

STANDARD PRODUCTS

| Part Code | No. of Power | USB | Dimensions |
|--------------|----------------|-------------------|-----------------|
| MINI DESK 2 | 2 x 5A sockets | N/A | 160 x 72 x 78mm |
| MINI DESK 1U | 1 x 5A sockets | Dual 5V 18W A+C | 160 x 72 x 78mm |
| MINI DESK U2 | N/A | 2x Dual 5V 3.4A A | 160 x 72 x 78mm |

INSTALLATION



All desktop units come with 2 methods of attaching to the desktop. Fix to the desk with either a pair of G-Clamps, or using adhesive pads.

The clamps come with an optional rubber guard to protect the desk

USAGE & MAINTENANCE

Not to be used with products and appliances exceeding 5A

Fuses are 5x20mm and can be user-replaced.

To replace a fuse, disconnect the unit from the mains first.

To clean unit, disconnect from the mains, and wipe with a clean damp cloth

TECHNICAL SPECIFICATION

| | |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| In the box | 1x Desktop unit; pair of clamps; pair of adhesive pads |
| Construction | PVC extrusion, PVC sockets and fascias |
| Max voltage | 250V |
| Fuse rating | 3.15A or 5A |
| Fuse size/type | 5x20mm ceramic slow blow |
| USB | USB output type A and type C, Max 18W USB A: QC3.0, DC 5V3A, 9V2A, 12V1.5A USB C: PD, DC 5V3A, 9V2A, 12V1.5A A+C together: DC5V3.4A |
| Mains lead length | 500mm |
| Mains lead spec | 1.5mm ² HO5VV-F |
| Mains connector | 20A male 3-pole connector |
| Conformities | BS 1363; BS 6396:2008; BS 5733; IEC60884-1:2006; UL 94V-0 |
| Switch | Single pole with neon indicator |
| Compliances | RoHS; WEEE; CE; UKCA |