



C19 PDUs

Picture shows 8 way horizontal C19 PDU

- IEC 320 C19 presentation
- Tough 1.5U aluminium extrusion
- Shrouded switch with switch cover
- C20, 16A commando, or 32A commando options

IEC C19 PDUs are commonly found in networking cabinets connecting directly to the targeted equipment. Many products use the C19 as it is an international standard and can deliver a higher output than the IEC C13. Many UPS's also use the C19 output.

Standard products

Order Code

Product Description

HC19/6

Horizontal PDU with 6 x IEC C19 sockets, 3m lead to IEC C20 plug


HC19/8

Horizontal PDU with 8 x IEC C19 sockets, 3m lead to IEC C20 plug

VC19/10

Vertical PDU with 10 x IEC C19 sockets, 3m lead to IEC C20 plug

PDU options



IEC C20 plug
IEC 60320(320)



16A commando plug
IEC 60309(309)



32A commando plug
IEC 60309(309)

PDU technical data

Weight of PDU	1.35kg – 1.65kg
Net length of PDU	486mm – 658mm
Net width of PDU	66mm
Net depth of PDU	44mm
Shipping length of PDU	540mm – 750mm
Shipping Width of PDU	122mm - 142mm
Shipping Depth of PDU	60mm – 68mm
Shipping Weight of PDU	1.5kg – 1.9kg
PDU max power	3250W
Output rating	16A
Overall rating	16A (internal wiring will be upgraded for 32A option)
Input Frequency	50/60Hz
Acceptable Input Voltage	250VAC